



Data Sheet

Control panel Type MMIGRS2CC

Electronic controller suitable for all HVAC/R software application needs.



MMIGRS2CC close control is MCX's family remote interface. It's fitted with a graphic display that allows a complete customization of the user interface. The connection with every unit of the MCX range is made through the CANbus network. All the information about the user interface is loaded inside the MCX controller; that's why there is no need of programming the MMIGRS2CC interface. MMIGRS2CC is powered externally or from the controller which it is connected to and automatically shows its user interface.

Features:

- Full graphic LCD display, 128 x 64 dots resolution
- Easy connection to MCX CANbus network through telephone plug and CAN connector
- No need to be programmed: information about user interface is loaded from the MCX controller
- Powered by the MCX which it is connected to
- Dimensions 88 x 150 mm
- · Panel and wall mounting
- IP64 protection rating on panel version
- 2 dedicated keys for easy access to alarm and ON/OFF functions
- 3 coloured back lighted keys: red, orange and green



Product specification

General features

Table 1: General features

Table 1. General reactives			
Features	Description		
Power supply	From the MCX through the RJ12 telephone connector		
	12 – 30 V DC SELV (separate power supply is recommended)		
	24 V AC +10% / -15% SELV (separate power supply is recommended)		
	Maximum power consumption: 1.5 W		
Plastic housing	Self extinguishing V0 according to IEC 60695-11-10 and glowing / hot wire test at 960 °C according to IEC 60695-2-12		
Ball test	125 °C according to IEC 60730-1 Leakage current: ≥ 250 V according to IEC 60112		
Operating conditions	CE: -20T60 / UL: -20T60, 90% RH non-condensing		
Storage conditions	-30T80, 90% RH non-condensing		
Integration	In Class I and / or II appliances		
Index of protection	IP64 ~ NEMA3R (panel version)		
	IP40 (wall version)		
Period of electric stress across insulating parts	Long		
Resistance to heat and fire	Category D		
Immunity against voltage surges	Category II		
Software class and structure	Class A		

Connection diagram – MCX or MCX06 connection

CANH-R connection should be done only on the first and last element of the network

Figure 1: MCX06D - MMIGRS2CC







Figure 2: MCX - MMIGRS2CC



• NOTE:

*When MMI is not connected to MCX via telephone cable, the autodetection feature of the MCX CAN address will not work.

Therefore check the following MMIGRS2CC setting:

- 1. Enter BIOS menu pressing and holding X + Enter keys for 5 seconds.
- 2. Select "MCXselection" \rightarrow "Manual Mode" and set the CAN address of the MCX you wish to connect to.

Connection

Table 2: Connection

Connectors	Туре	Dimensions
Power supply connector	24 V AC - 2 way screw plug-in connector type	 pitch 3.5 mm section cable 0.08 – 1.5 mm²
CAN connector	4 way screw plug-in connector type	 pitch 3.5 mm section cable 0.08 – 1.5 mm²
CAN-RJ connector	6/6 way telephone RJ12 plug type	



Dimensions

Figure 3: Panel mounting





Figure 4: Wall mounting



User interface

Table 3: User interface

Tuble 5. Oser meeridee				
Туре	Features	Description		
LCD display	Display	Graphical LCD blue transmissive		
	Backlight	White LED backlight adjustable via software		
	Contrast	Adjustable via software		
	Format	128 x 64 dots		
	Active visible area	66.5 x 33.2 mm		
Keyboard	Number of keys	6, of which 3 with respectively green, red, orange LEDs that can be individually managed via software		
	Keys function	Set by the application software		
Mounting	Panel mounting	See the drilling template in figure, using the screws supplied in the packaging		
	Wall mounting	Standard 3 modules box		



Ordering

Product part numbers

Table 4: Product part numbers

Description	Code No.
MMIGRS2, Close Control, Wall, S	080G0299
MMIGRS2, Close Control, Panel, I (27 pieces)	080G0298

• NOTE:

Both single pack codes (S) and industrial pack codes (I) include standard kit connector.

Accessories part numbers

Table 5: Accessories part numbers

Description	Code No.
ACCCBI, Telephone Cable User Interface Connector, 1.5 m Cable	080G0075
ACCCBI, Telephone Cable User Interface Connector, 3 m Cable	080G0076

Certificates, declarations, and approvals

The list contains all certificates, declarations, and approvals for this product type. Individual code number may have some or all of these approvals, and certain local approvals may not appear on the list.

Some approvals may change over time. You can check the most current status at danfoss.com or contact your local Danfoss representative if you have any questions.

Table 6: Certificates, declarations, and approvals

File name	Document type	Document topic	Approval authority
080R2089.02	EU Declaration of conformity	EMC directive 2014/30/EU: EN61000-6-3: 2007 +A1: 2011 EN61000-6-2: 2005 RoHS directive 2011/65/EU and 2015/863/EU: EN 50581: 2012	Danfoss
UL E31024	Electrical - Safety Certificate	-	UL



Online support

Danfoss offers a wide range of support along with our products, including digital product information, software, mobile apps, and expert guidance. See the possibilities below.

The Danfoss Product Store



The Danfoss Product Store is your one-stop shop for everything product related—no matter where you are in the world or what area of the cooling industry you work in. Get quick access to essential information like product specs, code numbers, technical documentation, certifications, accessories, and more.

Start browsing at store.danfoss.com.

Find technical documentation



Find the technical documentation you need to get your project up and running. Get direct access to our official collection of data sheets, certificates and declarations, manuals and guides, 3D models and drawings, case stories, brochures, and much more.

Start searching now at www.danfoss.com/en/service-and-support/documentation.

Danfoss Learning



Danfoss Learning is a free online learning platform. It features courses and materials specifically designed to help engineers, installers, service technicians, and wholesalers better understand the products, applications, industry topics, and trends that will help you do your job better.

Create your Danfoss Learning account for free at www.danfoss.com/en/service-and-support/learning.

Get local information and support



Local Danfoss websites are the main sources for help and information about our company and products. Find product availability, get the latest regional news, or connect with a nearby expert—all in your own language.

Find your local Danfoss website here: www.danfoss.com/en/choose-region.

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.